



DESCRIPTION: FLOOR-TO-WALL
 ALUMINUM: 6063-T5 EXTRUSION
 EXPOSED FINISH: MILL
 FILLER STRIP: CLOSED CELL NEOPRENE W/ ADHESIVE BACKING
 ZINC CHROMATE AREAS IN CONTACT W/ CONCRETE
 ALLOWABLE LOAD: 1528 LB/FT AT MAX OPENING
 MOVEMENT: ±25% JOINT WIDTH
 STOCK LENGTHS: 20'0"

K10-36-11
 REV. 06/09



Architectural Art
MANUFACTURING
 Division of Pittcon Architectural Metals, LLC
 283 SWANSON DRIVE, STE 103
 LAWRENCEVILLE, GA 30043
 PH: (678) 680-7373 FAX: (678) 735-0085
 TOLL FREE: (800) 835-0028 web: www.archart.com

<i>FL/WL BLOCK-OUT FILLER ALUMINUM</i>		
MODEL: K10-36-11		
DRAWN BY: JMT	SCALE: NTS	DRAWING NO.:
SHT. 1 OF 1	ISSUE DATE: 11/24/08	DTL-01

NO.	DESCRIPTION	BY	DATE
REVISIONS			
<small>The information contained herein is the proprietary property of ARCHITECTURAL ART MFG., Division of Pittcon Architectural Metals, LLC. No portion of it may be reproduced by any means or used in any form except for the purpose for which it was furnished. All rights of design and invention are hereby reserved. We reserve the right to make changes in the design at our discretion.</small>			