



DESCRIPTION: FLOOR FIRE BARRIER

- 2 HOUR RATED UL ASSEMBLY #FF-D-0072
- NORMAL, OR LIGHTWEIGHT CONCRETE
- SUITABLE EXPANSION JOINT COVER REQUIRED FOR LOAD BEARING APPLICATIONS
- MOVEMENT CAPABILITIES: \pm 50% JOINT WIDTH, CLASS II AND III
- "L" RATED FOR AIR LEAKAGE
- STOCK LENGTHS: 80'-0" ROLLS

P30-11-02 FLOOR
Architectural Art 01/07/11



**Architectural Art
 MANUFACTURING**

Division of Pittcon Architectural Metals, LLC
 283 SWANSON DRIVE, STE 103
 LAWRENCEVILLE, GA 30043
 PH: (678) 680-7373 FAX: (678) 735-0085
 TOLL FREE: (800) 835-0028 web: www.archart.com

RIGHTS OF DESIGN

All rights of design, detail, engineering and/or invention contained herein are the property of Architectural Art Mfg. and are not to be reproduced or provided to any other party. Architectural Art Mfg. reserves the right to amend or withdraw any information contained herein without notice and will not be liable for any inaccuracy or ambiguity of said information.

P30-11-02

2 HOUR FLOOR FIRE BARRIER

DRAWN BY: DOC	SCALE: NTS	DRAWING NO.:
SHT. 1 OF 1	ISSUE DATE: 01/07/11	DTL-01