



NOTE: AIR IS VACCUMED FROM SEAL PRIOR TO INSTALLATION ALLOWING MAXIMUM CONTACT BETWEEN JOINTCRETE EPOXY AND CONCRETE. UPON INSTALLATION VACCUM IS RELEASE ALLOWING AIR TO RETURN AND SEAL TO ADHERE TO CONCRETE.

STYLE	MVT.	NOM. "A"	MIN. "A"	MAX. "A"
W20-ES-SA	2 1/2" (62)	2" (51)	3/4" (20)	3 1/4" (83)
W30-ES-SA	3 1/4" (83)	3" (76)	1 1/4" (32)	4 1/2" (114)
W40-ES-SA	3 7/8" (98)	4" (102)	1 7/8" (48)	5 3/4" (146)

CHART BASED ON NOMINAL JT. OPENING @ 70 ° F
 () INDICATE DIMENSIONS IN MILLIMETERS

DESCRIPTION: FLOOR-FLOOR (EXTERIOR)
 EXPOSED FINISH: BLACK
 SANTOPRENE: 591-65A
 MOVEMENT: ±50% JOINT WIDTH
 STOCK LENGTHS: CONTINUOUS BETWEEN COLUMNS/DRAINS

W()-ES-SA
 FORMERLY W()-15-91



**Architectural Art
 MANUFACTURING**

Division of Pittcon Architectural Metals, LLC
 283 SWANSON DRIVE, STE 103
 LAWRENCEVILLE, GA 30043
 PH: (678) 680-7373 FAX: (678) 735-0085
 TOLL FREE: (800) 235-2222 web: www.archart.com

EPOXY BONDED EXPANSION SEAL

MODEL: W()-ES-SA

DRAWN BY:
 JW

SCALE:
 NTS

DRAWING NO.:

DTL-01

SHT. 1 OF 1

ISSUE DATE:
 08/05/08

NO.	DESCRIPTION	BY	DATE

REVISIONS

The information contained herein is the proprietary property of **ARCHITECTURAL ART MFG.**, Division of Pittcon Architectural Metals, LLC. No portion of it may be reproduced by any means or used in any form except for the purpose for which it was furnished. All rights of design and invention are hereby reserved. We reserve the right to make changes in the design at our discretion.